





TransAfrica Motors Ltd are the Sole Distributors of FAW Trucks in Kenya.

Our Branches:

Nairobi

Enterprise Road Tel: (020) 6550695

Mob: 0720 777 777

Mombasa

Jomo Kenyatta Avenue Tel: (041) 2491720/30 Mob: 0724 999 222

Kisumu

Obote Road. Tel: (057) 2026386

Mob: 0704 506 895

Nakuru

Nakuru - Nairobi Highway next Tuskys Hyrax

Tel: (020) 8068884 Mob: 0743 897 961

Eldoret

Along Nairobi Road Tel: (053) 2032525

Mob: 0775 550 450

TransAfrica Motors LTD is certified



Three (3) Spaner Rating















CA1073 (Tiger V 4x2)

G.V.W 6,800Kg

Overall Dimension(LxWxH) 6260x2250x2650

Min Ground Clearance 200mm
Engine Model CA498E3-12

Displacement 3.1L

Engine Type 4 cylinder inline, 4 stroke intercooled,

direct injection

Rated Power 90kW (120hp) @3200rpm

Clutch Dry type, single plate, diaphram spring

clutch, hydraulic controlled and air aided

power operating

Transmission 5 forward speeds and 1 reverse

Rear Axle FAW 1058 Press welding with single

reduction ratio 5.571

Wheel Base 3260mm
Tyre Size 7.00R16-12PR

Fuel Tank Capacity 90L

CA1081

Clutch

G.V.W 11,000kg

Overall Dimension(LxWxH) 8000x2480x2640

Min Ground Clearance

Engine Model CA6DF2D-17

Displacement 6.55L

Engine Type 6 cylinder inline, 4 stroke water cooled,

237mm

direct injection, turbo charged

Rated Power 132kW (170hp) @2300rpm

Dry type, single plate, diaphram spring clutch, hydraulic controlled

Transmission 6 forward speeds and 1 reverse

Rear Axle FAW 380 casting axle with single

reduction ratio 4.875

Wheel Base 4600mm

Tyre Size 9R22.5-14PR

Fuel Tank Capacity 160L



TIPPER TRUCKS

CA3223

G.V.W 26,000kg

 Overall Dimension (LxWxH)
 6775x2503x2760

 Inner Body (LxWxH)
 4800x2300x1200

 Engine Model
 CA6DF2D-23

Displacement 6.557L
Engine Type 6 cylinder inline, 4 stroke, water-cooled,

turbo charged, direct injection

Rated Power 170kW (230hp) @2300rpm

Clutch Dry type, single plate, diaphram spring

clutch, hydraulic controlled and air

aided power operating

Transmission 8 forward speeds and 1 reverse
Rear Axle FAW 435 single reduction, ratio 5.571

Wheel Base 3200+1350mm

Tyre Size 11R22.5-16PR
Fuel Tank Capacity 300L



CA3320 Tipper 6x4

Overall Dimension (LxWxH) Inner Body (LxWxH)

Engine Model Displacement

Engine Type

Rated Power Clutch

Transmission Rear Axle

Wheel Base Tyre Size

Fuel Tank Capacity

35,000kg

7818x2490x2890 5200x2300x1300

WP.10.290E32 9.726L

6 cylinder inline, 4 stroke, water-cooled,

turbo charged

213kW (290hp) @2200rpm

\$\phi\$ 430mm Dry type, single plate, diaphram

spring, hydraulic controlled and air

auxillary power supply

9 forward speeds and 1 reverse FAW 300 press welding with double

reduction ratio 5.92 3400+1350mm 315/80R22.5-20PR

400L



PRIME MOVERS



CA4181 New J5p 380hp 6x4 (Single Reduction)

Overall Dimension (LxWxH)

Engine Model

Displacement

Engine Type

Rated Power

Clutch

Transmission Rear Axle Wheel Base

Tyre Size

Fuel Tank Capacity

31,900kg

6798x2495x2990

WP.10.380E32

9.726L

6 cylinder inline, 4 stroke, water-cooled,

direct injection, turbo charged

280kW (380hp) @2200rpm

Dry type, single plate, diaphram spring, hydraulic controlled and air auxillary

power supply

12 forward speeds and 1 reverse FAW 457 single reduction ratio 4.444

3150+1350mm

315/80R22.5-18PR

600L

CA4322 J5p 380hp 6x4 (Double Reduction)

G.V.W

Overall Dimension (LxWxH)

Engine Model Displacement

Engine Type

Clutch

Rated Power

Transmission Rear Axle

Wheel Base

Tyre Size **Fuel Tank Capacity** 31,900kg

6798x2495x2990 WP.10.380E32

9.726L

6 cylinder inline, 4 stroke, water-cooled,

direct injection, turbo charged 280kW (380hp) @2200rpm

Dry type, single plate, diaphram spring, hydraulic controlled and air auxillary

power supply

12 forward speeds and 1 reverse Axle with double reduction ratio 5.921

3150+1350mm 315/80R22.5-18PR

600L

